



使用说明:

- A)、请按照说明书, 正确安装、摆放设备连接供水、排水管。在安装现场预留10mm的额外空间, 以满足安装要求。(风冷设备, 需要更多的空间, 以满足空气流通和热量排出)。
- B)、冰的产出取决于环境温度和水的水温。
- C)、可选配3cm、6cm、10cm、15cm高底脚。

Using instruction:

- A)、Please follow the instructions, properly install and place the equipment connect the water supply pipe, drain pipe, and reserve additional space 10mm at the installation site to meet the installation requirements. (Air cooling equipment needs more space to meet the air flow and heat discharge.
- B)、The production of ice depends on the ambient temperature and the temperature of the water.
- C)、Optional 6cm 10cm 15cm adjustable feet.

Item 名称	Commercial Ice Maker 商用制冰机
Model 型号	JM-1200
Electrical 电流	8.1A
Voltage 电源	220v/±10% 50Hz
Power 额定功率	2400w
Capacity 制冰能力	540kg/24h
	Air temp 环温20°C, Water temp 水温15°C
Ice Type 冰形	432kg/24h
	Air temp 环温32°C, Water temp 水温20°C
Ice Size 冰块尺寸	Crescent 月形冰
Storage 储冰量	30*13*38mm
Work Water Consumption 制冰耗水量	400kg
Condensing Water Consumption 冷凝耗水量	702KG/24h
Outside Material 外壳钣金材料	/
Ice Bin Material 储冰筒材料	304ss
Insulation Material 保温材料	PE
Ice Falling Mode 落冰方式	Cyclopentane 环戊烷
Water Feeding 进水方式	Heat Pump+Flow 热泵+流水
Drainage Mode 排水方式	4inch (R1/2)direct feeding water 4分R1/2直接供水
Power Connection Mode 电源连接方式	AD25 inch drain-pipe with cleaning 直径25分排水管带清洗
Water Supply Connection Mode 供水连接方式	Power Cord Direct Connection 电源线直连
Drainage Connection Mode 排水连接方式	AD4 Inch Water pipe, R1/2 Threaded Valve 4分 (R1/2)螺纹连接
Compressor Type 压缩机类型	AD25 inch drain-pipe AD25排水管 Nature flow 自然流出
Condensing System 冷凝器型式	Enclosed Unit 全封闭式压缩机
Refrigerant Throttle 制冷剂节流方式	Forced air cooling 强制风冷/water cooling 水冷
Refrigerant Type/weight 制冷剂类型/重量	Expansion valve 膨胀阀
Ice Making Control 制冰控制系统	R404a/520g*2
Defrosting Control System Mode 制冰/除霜控制方式	PC Board Control 主板控制
Ice-Filled Control Mode 冰满控制方式	Mechanical switch+ delay switch 机械开关+延时控制
Water Level Control Method 水位控制方式	magnetic switch 磁性开关
Electrical Protection 电器保护方式	Water float 水位浮球
Compressor Protection Mode 压缩机保护方式	6.3a Fuse Wire 6.3A保险丝
Head dimension 主机尺寸:	High voltage protection/2.8mpa 高压保护
N.W/GW 净重/毛重	566*692*742 (without adjustable leg) 不含高脚
Head packing size 主机包装尺寸:	/
Ice bin model 储冰桶型号:	655*785*835
Ice bin Capacity 储冰桶容量:	A-900
Ice bin size 储冰桶尺寸:	250kg
Ice bin packing size 储冰桶包装尺寸:	760*915*1045
Ice bin N.W/GW 储冰桶净重/毛重:	650*1050*1120
Spare Parts With Machine 随机附件	/
	Ice Shovel, Inlet Pipe, Drain Pipe 冰铲、进水管、排水管

Approved by European Ce and Cb.
本产品已通过CE, CB认证。

HISAKAGE®

Crescent 月形冰

JM-1200

View Orientation	视图方向	俯正	侧后	T F	L B	Revise Date 修订日期	Make Date 制图日期	REV
						/	2019-05-09	A

Remark : Product update and modify, there are different between original product and picture, pictures only for reference, the right of final interpretation belong to Hisakage.
备注: 产品改造升级, 实物与原图有差异, 图片仅供参考, 久景为最终解释权。