



- A: Do not cover the ventilation windows of machine.
 B: Do not cover the air inlet and air outlet in the inside of machine.
 C: Keep the condenser clean no sundries and dust on air inlet surface .
- A: 摆放过程中后通风窗不能有遮挡, 必须保证通风,
 B: 柜内摆放物品不能挡住前后出风口,
 C: 每月清洗冷凝器, 不能有杂物灰尘阻挡迎风面.

Item 名称	Push type freezer cabinet 推入式雪柜
Model 型号	BG-90/BG-90F
Dimension 外形尺寸	905*985*2460
Voltage 电源	220V/50Hz
Power 额定功率	750W/1050W
Temperature Range 温度	-6℃~+15/-15~-20℃
Cooling Type 制冷方式	Air cooling 风冷
Capacity 容积	/
Material 材质	Interior内胆: 304 Cabinet箱体: 304
Refrigerant Type 制冷剂类型	R134a/R404a
Refrigerant Throttling Mode 制冷剂节流方式	Capillary 毛细管
Keep Temp Material 保温物料	Cyclopentane 环戊烷
Defrost Water 化霜水	Automatic Evaporation System 自动蒸发
Compressor Type 压缩机类型	Enclosed unit 全封闭式
Condensing System 冷凝器类型	Forced air cooling 强制风冷
Evaporating Fan 蒸发器风机	Hood Motor 220V 罩极电机220V
Temperature Controller 温控	Pc board 电脑板
Defrost Time 除霜时间	Every four hour 每隔4小时一次
Compressor work temp 压缩机启动温度	4℃
Compressor protection type 压缩机保护方式	High temperature protection 高压保护
Wattage safety type 电源保护方式	Voltage changer/transformer 变压器
Heat Dissipation Type 散热方式	Front breasting / venting refrigeration system 制冰融霜板
Shelves 层架	/
Light 灯光	4500K
Condensing Unit 机组	Self-Contained 一体式
Electrical Protection 电源保护方式	/
Insulation Layer Thickness 保温层厚度	/
Using Temp 使用温度	10~28℃
Packing Size 包装尺寸	/
N.W/G.W/净重/毛重	/

Approved by European CE and CB
 已通过CE、CB认证。

HISAKAGE

Push type freezer cabinet
推入式雪柜

BG-90/BG-90F

视图方向
View Orientation

Over Look View
俯视图
Front View

Rear View
后视图
Catalog View
侧面图
Side View

Revise Date 修订日期
2019-1-17

Make Date 制图日期
2018-10-8

REV
A

Remark:Product update and modify,there are different between original product and picture,pictures only for reference,the right of final interpretation belong to Hisakage. 备注: 产品改型升级, 实物与图面有差异, 图片仅供参考, 久谦为最终解释权。